

**ALL CATEGORIES**

Class *	A	B	C	D	E
Ambient Temp. Range, °C	> 15	5 to 15	-5 to +5	-5 to -15	< -15
Vapour Pressure, kPa	45 - 60	55 - 70	65 - 80	75 - 90	85 - 105
T10, °C, max	65	60	55	50	45
T50, °C	77 - 100	77 - 100	75 - 100	70 - 100	65 - 100
T90, °C	130 - 175	130 - 175	130 - 175	130 - 175	130 - 175
EP, °C max.	205	205	205	205	205
E70, %	20 - 45	20 - 45	25 - 47	25 - 50	25 - 50
E100, %	50 - 65	50 - 65	50 - 65	55 - 70	55 - 70
E180, % min	90	90	90	90	90
D.I., max	570	565	560	555	550

\* 'Class' is based on the minimum expected ambient temperatures of the market and will vary by season.

**Notes:**

Ambient temperature ranges listed represent the condition the vehicle operator will encounter. Local regulations/standards may define classes based on expected temperatures from varying historical or statistical information sources applicable to their locale.

D.I. (Distillation Index) =  $(1.5 * T10) + (3 * T50) + T90 + (11 * \text{mass \% of oxygen})$ ; temperatures are in degrees Celsius.

The D.I. oxygenate correction does not apply to ethers, but limited data on LEV/ULEV vehicles suggest that ethers may require a similar oxygenate correction. The need for and the magnitude of the correction will be determined as more data become available. Preliminary data indicate that vehicles may need further volatility controls beyond what is currently specified.

**VAPOUR / LIQUID RATIO (V/L), T<sub>v/L</sub>=20**
**ALL CATEGORIES**

Class	Test Temperature, °C, min.	Applicable Temperature, °C
1	60	≥43
2	56	< 43
3	51	< 36
4	47	< 29
5	41	< 21
6	35	< 14

Vapour lock class is based on the 90th percentile maximum (applicable) daily temperature. The minimum test temperature of the gasoline for V/L=20 is provided for each vapour lock class. Limits to TV/L=20 are required to prevent hot fuel handling problems such as vapour lock, as discussed in the gasoline technical background under 'Volatility.' Additional information is provided in ASTM D4814.